

Email: sales@engineeringlabequipments.com

Product Name:

Precision Pressure Gauge Calibrator

Product Code:
ENGLABINGCAG3000031



Description:

Precision Pressure Gauge Calibrator

Technical Specification:

The equipment is self-contained and portable, so it may be used in lecture theatre demonstrations or as a master calibrator for the laboratory.

Dead weight testers are the basic primary standard used worldwide for the accurate calibration of pressure gauges, pressure transducers etc.

The instrument combines a low and high-pressure range provided by two pistons of different effective area. Calibration is accurate to within ±0.025% of reading.

The pressure in the system is produced by means of a capstan-operated hydraulic ram, balanced by dead weight acting upon a piston of known area.

Oil is used as the hydraulic fluid.

The pressure developed is applied to the gauge that is to be calibrated.

A spirit level and adjustable feet are provided to enable the operator to level the instrument.

A flotation indicator mounted on the top plate removes the guesswork when floating the piston.

A laboratory calibration certificate is supplied for each piston together with a traceable certificate of overall accuracy.

The instrument is supplied complete with necessary weights and a fitted carrying case. ?", ¼", ?", ½" BSP and NPT female adaptors are included together with spare seals and a quantity of oil.

The direct measurement of pressure (p=F/A)

Masses added are proportional to the target pressure

Calibration of pressure gauges by deadweight method to an accuracy better than 0.025% of reading Dual pistons enable calibration over a wide range of pressures

Portable, self-contained deadweight precision pressure gauge calibrator Calibration gauges with 1-1,200 bar range to ±0.025% of reading Minimum standard weight increment is 0.05 bar Supplied complete with laboratory calibration certificate Includes carrying case and weights



Engineering Lab Equipment India

2/2