

Product Name :
Consolidation Apparatus Single Gang

Product Code :
ENGLABINGCAG400012



Description :

Consolidation Apparatus Single Gang

Technical Specification :

Specifications:

A standard consolidation apparatus consists of :

A loading unit which can hold a maximum capacity of 20 kg per cubic metre.

The loading yoke is connected to a lever arm through a counter balance.

With a lever ratio of 1:1, the balance is mounted on a compact steel stand.

Oedometer, the fixed type Consolidation meter is an assembly that can be used for testing specimens that are of 60mm diameter and 20mm thickness along with the guide ring.

Porous stones at the top and bottom of the specimen.

Channel based and perforated pressure pad along with the gasket and water inlet are provided.

The water reservoir comes with a pinch cork and a plastic tube.

The set of weights can give a pressure of 10 kg per cubic metre.

The loading units are suitable for use with consolidation cells of various diameters and consolidation cells that are floating ring type.

Twenty three weights are given along with the apparatus:

1.00Kg per cubic metre - 5 nos

0.50 Kg per cubic metre - 6 nos

0.10 Kg per cubic metre - 5 nos

0.05 Kg per cubic metre - 7 nos

Accessories:

A Dial gauge: 0.0002 * 5 mm. to 0.002 * 5mm.
Extension of 40mm length.
50 Test form pads for single dimensional consolidation.



Engineering Lab Equipment India