

Product Name :
Precision Laboratory Incubator

Product Code :
ENGLABINGCAG4500018



Description :

Precision Laboratory Incubator

Technical Specification :

Precision High-Performance Incubators for sample protection and maximum usability
Precise Sterilization, Incubating and drying in one unit.
Better mineral or glasswool blanket insulation keeps the surface Instrument from being burnt.
Easy-to-use for digital interface and silicone gasket
Ideal large scale for labs culturing bacteria
3" fiberglass insulation temperature uniformity
Power surges built-in circuit breaker protects against
Internal electrical socket use of instrumentation within the incubator
Technical Parameters :
Temperature Range: Ambient to 70 °C
Temperature Stability: Microprocessor Based PID Temperature +-1°C Controller +- 0.5°C Or better
Housing Material: CRC or Powder Coated Mild Steel
Interior: Polish stainless steel 304 grade Sheet
Insulation: Glasswool or Ceramic Blanket
Duty Cycle: Continuous
Optional: Double colour gate for the top panel request
Digital Setting: 0.1 °C
Digital Resolution: 0.1 °C
Power Consumption: 220/230V Single Phase, AC +- 10% 50Hz and 3 phase 440V

Optional: Customer demand outer Stainless Steel 304 grade body
Front Door: Glasswool or mineral wool with glass door window
Digital Setting: 0.1 °C



Engineering Lab Equipment India