

**Product Name :**  
Precision Laboratory Incubator

**Product Code :**  
ENGLABINGCAG4500018



**Description :**

Precision Laboratory Incubator

**Technical Specification :**

Precision High-Performance Incubators for sample protection and maximum usability  
Precise Sterilization, Incubating and drying in one unit.  
Better mineral or glasswool blanket insulation keeps the surface Instrument from being burnt.  
Easy-to-use for digital interface and silicone gasket  
Ideal large scale for labs culturing bacteria  
3" fiberglass insulation temperature uniformity  
Power surges built-in circuit breaker protects against  
Internal electrical socket use of instrumentation within the incubator  
Technical Parameters :  
Temperature Range: Ambient to 70 °C  
Temperature Stability: Microprocessor Based PID Temperature +-1°C Controller +- 0.5°C Or better  
Housing Material: CRC or Powder Coated Mild Steel  
Interior: Polish stainless steel 304 grade Sheet  
Insulation: Glasswool or Ceramic Blanket  
Duty Cycle: Continuous  
Optional: Double colour gate for the top panel request  
Digital Setting: 0.1 °C  
Digital Resolution: 0.1 °C  
Power Consumption: 220/230V Single Phase, AC +- 10% 50Hz and 3 phase 440V

---

Optional: Customer demand outer Stainless Steel 304 grade body  
Front Door: Glasswool or mineral wool with glass door window  
Digital Setting: 0.1 °C



## Engineering Lab Equipment India