

Email: sales@engineeringlabequipments.com

**Product Name :** Humidity Chamber

Product Code: ENGLABINGCAG4500069



## **Description:**

**Humidity Chamber** 

## **Technical Specification:**

Double walled finish

Outside mild steel powder coated as well as puff insulation support

Stainless steel perforated adjustable shelves

Temperature control from 10oc to 60� c (+/- 5%)

Humidity control from 55% to 90% (+/- 5%)

Digitally controlled interface

Coming with wheel support for mobility

Provides working on 220 v ac supply

Chamber comprising highly polished stainless steel sheet finish

Inner compartment featuring stainless steel adjustable shelves

Quality motor blower for forced air circulation

Precision air ducting support for allowing positive air flow

System designed to maintain constant temperatures in chamber

For avoiding thermal loss, system comes with puff insulation provided between inner and outer walls

Equipment fitted with hermetically sealed compressor with CFC free refrigerant

2 doors support with inner full length transparent door

Available in sizes of 455 x 455 x 710, 605 x 605 x 605, 605 x 605 x 910mm (wxdxh)

Sturdy hinge support and magnetic gasket provided for double walled main door

Automatic temperature control provided through digital temperature controller and indicator

System supporting PID with pt. 100 sensor

**Technical Specifications:** 

MOC Outer: Mild Steel Powder Coated

MOC Inner: Stainless Steel

Safety: Thermostat Insulation: PUFF Temp.: 10oc to 60"¿½ c. Humidity: 55% to 90% +/- 5% Type: Forced Convection Type

Compressor: Hermetically Sealed Compressor

Temperature Control: Microprocessor Based Digital Temperature Controller Cum Indicator

Temperature Range: 5oc – 60oc +/-1oc Humidity Creation: By Steam Injection

Humidity Controller: Digital Humidity Indicator-Cum-Controller.

Humidity Range: 5% Above Ambient From 55% – 95%RH±3%RH At Cool Temperatures

Inner Size (WxDxH): 455 x 410 x 610mm, 505 x 415 x 830mm, 570 x 550 x 875mm, 650 x 580 x 900mm

Electric Supply: 220/230V AC, 50/60Hz

Applications:
Cosmetics Industry
Plant / Insect Growth
Packaging Industry



## **Engineering Lab Equipment India**