

Product Name :
Digital Double Door Drying Oven

Product Code :
ENGLABINGCAG4500074



Description :

Digital Double Door Drying Oven

Technical Specification :

This range of ovens is designed for drying large quantities of soil and aggregate samples and maintains temperature in accordance with most B.S. and ASTM requirements. The 225 Lts. and 425 Lts. are economy models constructed with coated mild steel exterior and Stainless Steel coated interior chamber, which is both durable and corrosion resistant.

These units meet the requirements of BS 1377 and are ideal for on-site laboratories and general soil and aggregate testing.

Technical Specifications :

Air-Flow Direction: Horizontal Air Flow, Dual Air Flow

Capacity: 100-500 Kg, 500-1000 Kg

Material for Construction: Stainless steel

No. of Shelves: 3

Type: Cabinet Ovens, Belt Conveyor Oven

Max Temperature (C): 200-300, 300-400

Options And Accessories:

Dial thermometer with collar fixing for door

Heavy duty shelves (on Request at an extra price)

Color of the Oven (Only on qty. greater than 3 Units)

The larger soil drying ovens are constructed with mild steel and powder coated exterior and Stainless Steel coated chamber which is both durable and corrosion resistant.

Door locking arrangement is very easy convenient with lever to lock unlock with half turn lever
A Safety Thermostat is fitted inside the Oven for safety purpose.
In case of the failure of the PID controller the safety thermostat will serve as the temperature controller.
A High / Low switch is fitted on the panel of the Oven for Heaters.
This feature allows heaters to burn all together or half of them.
The Least Count Division for viewing / setting the Temperature is 0.1° C
All Sizes of Oven are fitted with a (PID Controller) having a microprocessor digital control as standard.
Wiring of heaters can be connected / dis-connected removing the side panels of the Oven.
Caster wheels with locking arrangement are fitted below the Oven for easy movability of the unit from one place to another.
All units come with MCB tripping device in cases of any short circuit, overloading of voltage and Low voltage cut off.



Engineering Lab Equipment India